




SERIES 6000 SINGLE ROW BALL BEARINGS




OPEN




ZZ



-2RS



-2RSV



NR

Bearing No.	Bore - d		Outer Diameter - D		Width - W		Radius - r	
	mm	in.	mm	in.	mm	in.	mm	in.
6000	10	0.3937	26	1.0236	8	0.3150	0.50	0.020
6001	12	0.4724	28	1.1024	8	0.3150	0.50	0.020
6002	15	0.5906	32	1.2598	9	0.3543	0.50	0.020
6003	17	0.6693	35	1.3780	10	0.3937	0.50	0.020
6004	20	0.7874	42	1.6535	12	0.4724	1.00	0.039
6005	25	0.9843	47	1.8504	12	0.4724	1.00	0.039
6006	30	1.1811	55	2.1654	13	0.5118	1.50	0.059
6007	35	1.3780	62	2.4409	14	0.5512	1.50	0.059
6008	40	1.5748	68	2.6772	15	0.5906	1.50	0.059
6009	45	1.7717	75	2.9528	16	0.6299	1.50	0.059
6010	50	1.9685	80	3.1498	16	0.6299	1.50	0.059
6011	55	2.1654	90	3.5433	18	0.7087	1.50	0.059
6012	60	2.3622	95	3.7402	18	0.7087	2.00	0.079
6013	65	2.5591	100	3.9370	18	0.7087	2.00	0.079
6014	70	2.7559	110	4.3307	20	0.7874	2.00	0.079
6015	75	2.9528	115	4.5276	20	0.7874	2.00	0.079
6016	80	3.1496	125	4.9213	22	0.8661	2.00	0.079
6017	85	3.3465	130	5.1181	22	0.8661	2.00	0.079
6018	90	3.5433	140	5.5118	24	0.9449	2.50	0.098
6019	95	3.7402	145	5.7087	24	0.9449	2.50	0.098
6020	100	3.9370	150	5.9055	24	0.9449	2.50	0.098
6021	105	4.1339	160	6.2992	26	1.0236	3.00	0.118
6022	110	4.3307	170	6.6929	28	1.1024	3.00	0.118
6024	120	4.7244	180	7.0866	28	1.1024	3.00	0.118
6026	130	5.1181	200	7.8740	33	1.2992	3.00	0.118
6028	140	5.5118	210	8.2677	33	1.2992	3.00	0.118
6030	150	5.9055	225	8.8583	35	1.3780	3.50	0.138
6032	160	6.2992	240	9.4488	38	1.4961	3.50	0.138
6034	170	6.6929	260	10.2362	42	1.6535	3.50	0.138
6036	180	7.0866	280	11.0236	46	1.8110	3.50	0.138
6038	190	7.4803	290	11.4173	46	1.8110	3.50	0.138
6040	200	7.8740	310	12.2047	51	2.0079	3.50	0.138